

# MT1135


TECHNICAL DATA SHEET





 **MANITOU**

[www.manitou.com](http://www.manitou.com)

# MT 1135

	MT 1135	MT 1135 H	MT 1135 HA
<b>Lifting</b>			
Max. capacity		3500 kg	
Max. lifting height		11.05 m	
Max. outreach		7.75 m	
Break-out force with bucket		6305 daN	
<b>Unladen time</b>			
Lifting		8.5 secs	
Lowering		7.0 secs	
Extension		13.0 secs	
Retraction		9.0 secs	
Crowd		3.0 secs	
Dump		3.0 secs	
<b>Tyres</b>		400/80-24	
<b>Braking</b>			
Service brake		Oil immersed multi-disc braking on front/rear axles	
Parking brake		Automatic Negative Handbrake	
<b>Engine</b>			
		PERKINS - STAGE 3B	
Type		854E-34TA	
Cubic capacity		3400 cm <sup>3</sup>	
Power		102 HP/75 kW	
Max. torque		420 Nm - 1400 rpm	
Injection		direct	
Cooling		water	
Laden drawbar pull	9150 daN		7150 daN
	torque converter 4 wheel drive		hydrostatic 4 wheel drive
<b>Transmission</b>			
Reversing shift		electrohydraulic control	
Number of gears (forward/reverse)	4/4		3/2
Max. travel speed (may vary according to applicable regulations)		25 kph or 35 kph	
Steering mode		4 wheel steer - 3 Steering Modes	
			
<b>Controls</b>			
		JSM® Joystick multi - function Load Limiter Cut off system - EN15000 Norm	
<b>Hydraulics</b>			
Pump		gear type with priority valve 125 l/min - 270 bar	
<b>Capacities</b>			
Hydraulic oil		175 l	
Fuel		120 l	
<b>Unladen weight (with forks)</b>	8800 kg		8900 kg
<b>Dimensions</b>			
1. Front wheel centre to carriage		1.60 m	
2. Wheelbase		2.88 m	
3. Rear wheel centre to rear face		0.89 m	
4. Overall length to carriage		5.37 m	
5. Ground clearance		0.41 m	
6. Overall width of cab		0.88 m	
7. Inside tyre width		1.87 m	
8. Overall width		2.28 m	
9. Overall width (stabilizers lowered)		2.28 m	
10. Overall height		2.42 m	
Standard forks (length x width x thickness)		1200 x 125 x 45 mm	
Turning radius (over tyres)		3.85 m	
Frame levelling		+/- 10°	
Carriage rotation (crowd/dump)		16°/110°	
<b>Noise and vibration</b>			
Noise at driving position (LpA)		82 dB	
Environmental noise (LwA)		106 dB	
Vibration to whole hand/arm		<2.5 m/s <sup>2</sup>	




# MT1135


## Rough terrain load chart

standard EN1459 annex B

### Machine on tyres with forks




### Machine on stabilizers with forks



### Machine on stabilizers with platform

(MT 1135 HA version)



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,547,824 euros - 857 802 508 RCS Nantes



Your nearest **MANITOU** dealer:



Head office:  
B.P. 249 - 430 rue de l'Aubinière - 44158 Ancenis Cedex - France  
Tel: 00 33 (0)2 40 09 10 11 - Fax: 00 33 (0)2 40 09 10 97  
[www.manitou.com](http://www.manitou.com)