

Technical sheet

MLA 3-35 H

Articulated loaders



Capacities	Metric
Static tipping load with bucket (straight)	1670 kg
Static tipping load with bucket (full turn)	1280 kg
Static tipping load with forks (straight)	1169 kg
Static tipping load with forks (full turn)	909 kg
h35 - Max. height of bucket pivot point	2.86 m
h3 - Max. lifting height (below forks)	2.65 m
Breakout force with bucket	2540 daN
Weight and dimensions	
Unladen weight (with forks) with 2-post canopy	2472 kg
Unladen weight (with forks) with 4-post canopy	2520 kg
Unladen weight (with forks) with cab	2649 kg
m4 - Ground clearance	0.24 m
l2 - Overall length to carriage (with hitch)	3.35 m
y - Wheelbase	1.63 m
b21 - Overall width of 2 posts canopy	1.01 m
b22 - Overall width of 4 posts canopy	1.02 m
b4 - Overall width of cab	1.02 m
b1 - Overall width (over tyres)	1.32 m
h36 - Overall height with FOPS removed and ROPS folded	1.78 m
h37 - Overall height with 2 posts canopy	2.48 m
h38 - Overall height with 4 posts canopy	2.26 m
h17 - Overall height with cab	2.26 m
a4 - Crowd angle	39.70 °
a5 - Dump angle	43 °
Wa1 - External turning radius (over tyres)	2.63 m
Articulation angle	45 °
Standard tyres	Mitas - 31x15.5-15 SK-02
Engine	
Brand	Yanmar
Environmental norm	Stage 3A
Model	3TNV88
Number of cylinders - Cubic capacity	3 - 1600 cm ³
Power	35 hp / 26 kW
Max. torque	102.70 Nm at 1680 rpm
Transmission	
Type	Hydrostatic
Number of Gears (Forward) with standard speed	2
Number of Gears (Reverse) with standard speed	2
Number of Gears (Forward) with max. speed	2
Number of Gears (Reverse) with max. speed	2
Max. travel speed	19 km/h
Differential lock	Limited slip differential on front and rear axles
Parking brake	Manual parking brake
Hydraulics	
Hydraulic pump type	Gear pump
Hydraulic flow - Pressure	45 l/min - 207 bar
Drive hydraulic system pressure	345 bar
Tank capacities	
Hydraulic oil	26 l
Fuel	57 l
Noise & vibration	
Vibration to whole hand / arm	2.5 m/s ²
Miscellaneous	
Safety	Cab ROPS - FOPS Level 1

Options / Finishing

S : Standard / O : Optional / - : Not available

	Essential	Classic	Premium	Elite
General				
Hand throttle	S	S	-	-
Air prefilter	S	S	-	-
Comfort				
Tuner car radio	-	S	-	-
Mechanical seat	S	S	-	-
Canopy	S	-	-	-
Closed cab with heating	-	S	-	-
Adjustable steering column	S	S	-	-
Floor mat	-	S	-	-
Hydraulic				
Attachment hydraulic locking	O	O	-	-
Easy Connect System (ECS)	S	S	-	-
Continuous flow hydraulics	S	S	-	-
Attachment hydraulic line	S	S	-	-
Electricity / Safety				
Complete road lighting	O	S	-	-
Rotating beacon light	O	O	-	-
Front and rear work lights on cab (x4: 2 front + 2 rear)	S	S	-	-



Siège Social
430 rue de l'Aubinière - 44150 Ancenis Cedex - France
Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,547,824 euros - 857 802 508 RCS Nantes