



Technical sheet

MT 420 H


Telehandlers



Capacities	Metric
Max. capacity	2000 kg
Max. lift height	4.30 m
Max. reach	2.65 m
Bucket breakout force	1886 daN
Weight and dimensions	
l2 - Overall length of fork carriage	3.63 m
b1 - Overall width	1.49 m
h17 - Overall height	1.90 m
y - Wheelbase	2.13 m
m4 - Ground clearance	0.24 m
b4 - Overall cab width	0.79 m
Wa1 - Frame outer turning radius	2.98 m
Unladen weight (with forks)	4260 kg
Standard tyres	Pneumatic
Standard forks	1200 x 100 x 40
Performances	
Lifting	5 s
Lowering	3 s
Telescope extension	4.80 s
Retracting the telescope	3 s
Scoop	3.30 s
Dump	2.70 s
Engine	
Brand	Kubota
Environmental standards	Stage 3A
Number of cylinders - Capacity	4 - 2615 cm ³
Power	49 hp / 36 kW
Max. torque	170 Nm at 1600 rpm
Laden drawbar pull	2850 daN
Transmission	
Type	Hydrostatic
Number of gears (forward/reverse)	2/2
Parking brake	Automatic negative parking brake
Hydraulics	
Type of pump	Gear pump
Tank capacities	
Engine oil	10.20 l
Hydraulic oil	70 l
Fuel	60 l
Cooling liquid	8.60 l
Noise & vibration	
Noise at driving position (LpA)	76 dB(A)
Noise to environment (LwA)	104 dB(A)
Vibration on hands/arms	<2.50 m/s ²
Miscellaneous	
Steering wheels / Driving wheels	4 / 4
Safety	Standard EN 15000 Cab ROPS - FOPS Level 1
Controls	JSM



Load chart





Groundwater Lift Trucks Ltd,
Spurryhillock Industrial Estate,
Stonehaven, Aberdeenshire, AB39 2NH
01569 763247
sales@groundwater.uk.com
www.groundwater.uk.com



Siège Social
430 rue de l'Aubinière - 44150 Ancenis Cedex - France
Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,547,824 euros - 857 802 508 RCS Nantes