

Hand pallet truck 2.0 ton

BT lifter with Scale



Hand pallet truck

Truck specifications					LHM200SC
Identification	1.1	Manufacturer			BT
	1.2	Manufacturer's type designation			LHM200SC
	1.4	Operator type			Hand
	1.5	Load capacity/rated load	Q(t)	kg	2000
	1.6	Load centre distance	c	mm	600
	1.8	Load distance, centre of drive axle to fork	x	mm	925 ¹⁾
	1.9	Wheelbase	y	mm	1170 ¹⁾
Weight	2.1	Service weight		kg	103
	2.2	Axle load, with load, drive/castor/fork wheel		kg	375/805
	2.3	Axle load, without load, drive/castor/fork wheel		kg	20/10
Wheels	3.1	Steer/fork wheels: Powerthane (Po), Steel (S), Nylon (N), Polyurethane (P), Rubber (R), Rubber antistatic (Ra)			N, P, S, Po, R, Ra / N, P, Po
	3.2	Wheel size, front			175x60
	3.3	Wheel size, rear			85x100 / 85x75 ²⁾
	3.5	Wheels, number front/rear (x=driven wheels)			2/2 or 2/4 ²⁾
	3.6	Track width, front	b ₁₀	mm	132
	3.7	Track width, rear	b ₁₁	mm	370/530
	Dimensions	4.4	Lift	h ₃	mm
		Lift height	h ₂₃	mm	205
4.9		Height of tiller in drive position, min./max.	h ₁₄	mm	1220
4.15		Height, lowered	h ₁₃	mm	90
4.19		Overall length	l ₁	mm	1520
4.20		Length to face of forks	l ₂	mm	370
4.21		Overall width	b ₁ /b ₂	mm	540/700 ³⁾
4.22		Fork dimensions	s/e/l	mm	65/170/1150 ⁴⁾
4.25		Width over forks	b ₅	mm	540/700 ³⁾
4.32		Ground clearance, centre of wheelbase	m ₂	mm	25
4.33		Aisle width for pallets 1000 x 1200 crossways	A _{st}	mm	1525 ¹⁾
4.34		Aisle width for pallets 800 x 1200 lengthways	A _{st}	mm	1725 ¹⁾
4.35		Turning radius	W _a	mm	1370 ¹⁾

1) Distance with forks raised

2) Single wheel / Boggie wheel

3) Other widths available on request

4) Other fork length available: 810/910/1000/1070/1220

All data are based on table configuration. Other configurations may give other values.

Truck performance and dimensions are nominal and subject to tolerances.

Specifications are subject to change without notice.

Scale data	Graduation multi-range			
	0 — 200		kg	0,2
	200 — 500		kg	0,5
	500 — 2000		kg	1,0
	Maximum inaccuracy, applied weight		kg	0,1
	Battery			12 Vdc/ 1,2 Ah
	Charger			230 V/ 12 Vdc

Dimensional drawings

BT lifter with Scale



