

SPECIFICATION

Truck Specification	Bendi Model	<b>B315 50 Electric powered AC Articulated Forklift Truck – 8 off</b>
	Basic Capacity	1500kg @ 500mm L/c to 3300mm
	Capacity @ 5M Lift @ 500mm L/c	1250kg @ 5M
	Max mast lift height	5000mm
	Closed Height	2599mm
	Extended Height	5849mm
	Free Lift	1750mm
	Mast Type	Triple Full Free Lift
	Height to Overhead Guard	2250mm
	Truck Length	2700mm
Truck Width	1150mm	
Fork Length – site preference	<b>950mm</b>	
Kettle Sites Details	Existing top beam	4570mm
	External door height / Ceiling height	4000mm+
	Rack tunnel clear height to u/s beam	n/a
	Existing transfer aisle	3000mm
	Existing rack to rack aisles	2070mm
	Existing rack frame depths	900mm
	Existing load to load aisles	1970mm
	Pallet orientation	stored 1000mm deep into racks
	Existing site pallets	1200 x 1000
	B3 Bendi aisle capability - Load to Load	<b>From 1600mm</b>
Site end of aisle clearances	1000mm+	
Pallet	Pallet/Load Depth	<b>1000mm deep into rack</b>
	Pallet/Load Width	<b>1200mm fork entry</b>
Power	Battery Quantity / Capacity	Two off / 630 Amp hour, 48 Volt (autofill)
	6.1/2 – 7 hour HF three phase charger	Supply only
	Supply Voltage	415 - 440 Volt
Features	Specification includes	<b>Chargers require type D circuit breakers</b> <b>AC Controller</b> , Slim front + over rotation for unique Bendi aisle safety and efficiency Sideshift, rev. alarm & mirror, beacon, BDI, hour meter, horn, twin front spots, creep button, spare battery c/w can & autofill cells OHG modified to allow crane out of battery – battery tank to have lugs to suit